

# LANDA®

Industrial Pressure Washers  
...Built Right to Do the Job Right

Since 1969

# NG

## Natural Gas-Heated, Hot Water Generator That Attaches to a Cold Water Pressure Washer

- Up to 3,000 PSI
- Increases incoming water temperature by up to 150°F
- Sch. 80 Heating Coil
- LP Conversion Option

NG-3000LM  
COMES WITH  
**MODULATING  
GAS VALVE**  
FOR CONSISTENT  
TEMPERATURE



**NG-3000LM**  
Shown with optional support table



**NG-3000**



■ **Triple Safety Protection**, including a rupture disk, high-limit thermostat and flow switch to prevent the build up of excessive pressures or heat.

■ **Rugged 12-gauge steel Chassis** protected by weather-resistant epoxy powder coat paint.

■ **Modulating Gas Valve** adjusts gas flow to keep temperature consistent at higher flow rates (NG-3000LM only)

■ **High-efficiency Burner** with millivolt ignition and standing pilot; also Honeywell gas valve

### Why Choose the NG Hot Water Generator

The NG-3000 is a stationary, natural gas-heated hot water generator that can be attached to a cold-water pressure washer making it a hot water washer.

The NG-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate—so it can be used for cleaning the toughest of cleaning challenges.

There are two models—NG-3000 and NG-3000LM—the “LM” version being much larger with a modulating gas valve, able to heat water at flow rates of up to 10.6 GPM. Both models can be converted to LP gas.

The NG models are packed with *Landa* quality throughout, including Schedule 80 heating coil, high-efficiency burner, rugged steel frame and a raised platform for easy positioning in a shop.

■ **Extra-durable Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.

■ **Helpful Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.

■ **9 feet of wire-braid, Hose** with coupler for connecting to cold water pressure washer.

### NG-3000 and NG-3000LM Specifications

Feature	NG-3000	NG-3000LM
Part Number	1.103-901.0	1.103-902.0
GPM	Up to 6	Up to 10.6
PSI	Up to 3,000	Up to 3,000
Temperature Rise*	Up to 150° F	Up to 150°F
Heating Coil	1/2" Sch 80 / 154 ft.	3/4" Sch 80 / 360 ft.
Inlet Hose	3/8" I.D. x 9 ft.	1/2" I.D. x 9 ft.
BTU Per Hour	420,000	800,000
Dimensions LxWxH	31" x 24" x 46"	34" x 45" x 60"
Ship Weight	450 lbs.	900 lbs.

\* Variable depending on flow rate (3-10 GPM)

### OPTIONS:

Part No.	Description
<b>9.801-042.0</b>	Kit to convert fuel to LP gas for NG-3000 model
<b>8.904-068.0</b>	Kit to convert fuel to LP gas for NG-3000LM model
<b>8.912-689.0</b>	Support table, 8" (for NG-3000LM)

# LANDA®

Distributed by:

[www.landa.com](http://www.landa.com)