

LANDA®

Industrial Pressure Washers
...Built Right to Do the Job Right

Since 1969

AVAILABLE IN
**STAINLESS
STEEL &
MILD STEEL
CABINETS**

SEA

Stationary, Electric-Powered,
Cold Water Pressure Washer

- Up to 4.2 GPM
- Up to 3000 PSI
- Stainless Steel or Mild Steel Cabinet
- Accepts Hot Water Up to 185°F

■ **Industrial-grade Motor** is connected to the rugged, class-leading, tri-plunger, oil-bath **Landa LT** (stainless steel model) or **LM** (mild steel model) **High-Pressure Pump** (with 7-year warranty) by dual, heat-dissipating V-cogged belts. **Pulleys** are made of cast iron and can be easily adjusted by turning two bolts.

■ **Four quick-couple Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 0°, 15°, 25°, 40°.

■ **Heavy-duty Cabinet** rides on four **Rubber Feet** for absorption of vibration.

■ **Inlet Filter** strainer protects pump from debris.

■ **50 ft. of double steel-wire braid High Pressure Hose** with **24-inch Hose Guard** for burst protection and swivel crimp fitting for tangle-free handling of hose and trigger gun.



SEA3-11024D
Shown with mild steel cabinet

▶ Add portability to the SEA with optional **Wheel Kit** (stainless steel model #8.904-527.0 or mild steel model #9.801-031.0), including detergent jug holder. Optional **Hose Reel** (#8.903-521.0) provides tangle-free handling of up to 100 ft. of high-pressure hose.



■ **Many Safety Features**, including a thermal pump protector to prevent the build up of excessive pressures or heat.

SEA3-11024D

Shown with stainless steel cabinet



■ **Easy-to-attach Detergent Injector** for easy application of soap.

■ **Helpful Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ **Time-Delay Shutdown** (stainless steel model only) automatically turns off unit, if not in use for a set time, for protection against unattended operation.

■ **With the switch in the 'ON' position**, the optional **Auto Start/Stop** function allows the unit to be turned on with the pull of the trigger for convenient remote operation. (This option replaces Time-Delay Shutdown.)

■ **Insulated, fatigue-free, spring-loaded, 5000 PSI Trigger Gun** with dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.

■ **Optional rust-free Float Tank** with stainless steel inlet filter and backflow protection (stainless steel model only and cannot be ordered with wheel kit option).

■ **36 ft. of high-grade Electrical Cord** with **Ground Fault Circuit Interrupter** (on single-phase models) for operator safety.

■ **Compact Design**, 26" L x 20" W x 16" H.

■ **Easily handles Water Up To 185°.**

www.landa.com



WHY CHOOSE LANDA'S SEA

The SEA is the absolute top-of-the-line stationary, cold water pressure washer on the market today. The SEA features a Landa belt-drive pump with U-seals. Quiet and safe, Landa's electric-powered SEA is perfect for indoor cleaning applications.

QUALITY: Only the highest quality components are found in the SEA, including the Landa tri-plunger high-pressure pump with 7-year warranty, stainless steel or mild steel cabinet riding on four vibration-absorbing feet, and stainless steel variable pressure wand for maximum cleaning flexibility. Also, the SEA is assembled in a factory certified to the internationally recognized ISO-9001 quality standards.

SAFETY: The SEA is certified to the rigid UL-1776 and CSA G22.2 #68 safety standards. It also meets the National Electric Code (NEC), Canadian Electric Code (CEC), and complies with OSHA Regulation 1910.399, making it very safe to operate. The SEA comes equipped with magnetic contactor switch with thermal overload protection, time-delay shutdown (stainless steel model), 24-inch hose guard for burst protection, Ground Fault Circuit Interrupter on all single-phase models, and tri-lingual operating instructions.

APPLICATIONS: Landa's SEA is the perfect cleaning solution for use within the food service and automotive industries. If hot water cleaning is required, it can easily pair with Landa's EHW, NG, and HS heating modules.

SEA Specifications

Model #	Part # Stainless Steel	Part # Mild Steel	GPM	PSI	RPM SS/MS	Electrical V/PH	Amps SS/MS	Motor HP	Cord Length	Ship Wt SS/MS
SEA3-11024D	1.106-500.0	1.106-583.0	2.8	1000	1479/1479	120/1	20/20	2.0	36' w/ GFCI	205/210
SEA4-20024A	1.106-501.0	1.106-584.0	4.2	2000	1028/1300	230/1	28/29	6.2	36' w/ GFCI	280/285
SEA4-20024B	1.106-502.0	1.106-585.0	4.2	2000	1028/1300	230/3	16/19	6.2	10'	220/255
SEA4-20024C	1.106-503.0	1.106-586.0	4.2	2000	1028/1300	460/3	7.2/11	6.2	10'	220/260
SEA4-20024G	1.106-505.0	-	4.2	2000	1028	208/1	30/-	6.2	36' w/ GFCI	297/-
SEA4-20024H	1.106-506.0	1.106-587.0	4.2	2000	1028/1300	208/3	18.5/16	6.2	10'	220/265
SEA4-30024B	1.106-507.0	1.106-588.0	3.5	3000	917/1041	230/3	21.5/19	7.5	10'	235/275
SEA4-30024C	1.106-508.0	1.106-589.0	3.5	3000	917/1041	460/3	10.5/11	7.5	10'	235/270

Note: We are constantly improving and updating our products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. Landa product performance is certified by the Cleaning Equipment Trade Association (CETA) to be within 5% of listed specifications.

LanCom Wireless Remote Control Option Stainless Steel Models Only

- Remotely controls pump, burner, and injection of detergent from 1-2 sources
- Controls from up to 300 feet away
- Saves energy with easy shut down of unit when not in use
- Saves time in changing commands while away from the main unit

**TWO
WIRELESS
REMOTE
OPTIONS!**

Field Installed Options & Accessories:

Part #	Old Part #	Description
ALL MODELS		
8.903-040.0		24" Floor Stand
9.801-034.0	35-560	36" Floor Stand
8.903-617.0	30-635	36" Floor Stand (Stainless Steel)
9.801-035.0	35-563	Caster Wheels
9.801-036.0	35-565	E-Zee Hose Reel Kit
8.903-521.0	30-5020	E-Zee Hose Reel & Mounting Kit (Fits Wheel Kit)
9.801-031.0		Wheel Kit & Detergent Rack
8.903-619.0	30-640	Wall Mount Bracket Assembly (Stainless Steel)
9.801-033.0		Wall Mount Bracket Assembly (Mild Steel)
8.711-860.0	4-02750002	Hose Reel, Mini, 100 ft. (Fits Wall Bracket)
9.802-265.0	4-02750003	Hose Reel, Mini, 150 ft. (Fits Wall Bracket)
STAINLESS STEEL MODELS ONLY		
8.930-131.0		Wall Mount Bracket for Fixed LanCom Remote
8.904-527.0	4-03177	Wheel Kit with Detergent Rack (Stainless Steel)*
8.930-163.0		LanCom Wireless Remote Control, 1-Step Detergent▲†
8.930-177.0		LanCom Wireless Remote Control, 2-Step Detergent▲†
8.903-461.0	30-415	Remote On/Off Switch Option (Time-Delay units only)▲††
8.930-358.0		Additional Remote
8.903-448.0	30-332	Float Tank Option with Inlet Soap Injection▲*†
8.903-511.0	30-487	Automatic Start/Stop (Replaces Time-Delay Shutdown)▲†
MILD STEEL MODELS ONLY		
9.801-013.0		Hour Meter▲
9.801-012.0		Time-Delay Shutdown▲
9.801-011.0		Automatic Start/Stop▲*

▲ Factory Installed
†† Not compatible with LanCom

* Float Tank cannot be ordered with Wheel Kit
† Not compatible with Auto Start/Stop or Float Tank options

LANDA® Distributed by: