

LANDA®

Since 1969

Industrial Pressure Washers
...Built Right to Do the Job Right

SLX-SLT

The Only Portable Hot Water Pressure Washer
that Delivers 200°F Cleaning at up to 9.8 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil



■ Extra-large **Heating Coil** made of cold-rolled, 3/4" Schedule 80 steel pipe with 5-year warranty; features **Stainless Steel Top Wrap**; unique lift-out design for easy and quick **Coil Access**.

■ Rugged 2" x 4" x 1/8" thick box steel frame, with compact footprint, shields key components; further protected by weather-resistant **Epoxy Powder Coat** finish; **Power Platform** is vibration isolated to minimize frame stress.

■ Water-resistant, recessed metal **Control Panel** has adjustable thermostat, combination hour meter and tachometer, volt meter, burner switch and tri-lingual operating instructions for added safety.

■ Industrial-duty tri-plunger **Landa Pump** designed to run at low RPM for long life, 7-year warranty, with single-rail true-track **Pulley Adjustment**.

■ **Illustrated Warning Labels** universally understandable for liability protection.

■ 30-gallon diesel and 16-gallon gasoline **Fuel Tanks** (15-gallon diesel and 10-gallon gasoline on SLT) provide hours of uninterrupted operation; with elevated fuel lines to avoid suctioning of settled debris.

■ 50 ft. of double-wire braid **High Pressure Hose** rated for up to 6,000 PSI and featuring a 24-inch safety hose guard for operator burst protection.

■ High-efficiency **Burner**, with adjustable numbered dial-in air flow has a **Fuel-Water Separator** for fuel pump protection.

■ **Many Safety Features**, including a rupture disk, thermal pump protector, flow switch, unloader valve, and safety lock on the trigger gun.

■ Corrosion-resistant **Float Tank** (field installed kit) has stainless steel inlet filter and 3/4" float valve with anti-siphon backflow protection; also allows for introduction of detergents in high-pressure mode.

■ Insulated, fatigue-free **Trigger Gun**, with swivel crimp fitting for a tangle-free hose. Stainless steel, dual-lance **Variable Pressure Wand** features an ergonomic design and easy adjusting of the water pressure while cleaning.

■ Efficient **2,900-Watt Generator** produces reliable power for burner.

■ Adjustable **Detergent and Steam Valves** (field installed kits) provide precise metering of soap and on-demand wet-steam cleaning.

■ Gasoline-powered **Honda Engines**, or water-cooled, diesel-powered **Kubota Engines** all come with keyed electric starter for easy start-up and protection against unauthorized use; polyurethane **Battery Box** with vibration isolators protects and firmly secures battery (battery not included).



SLT8-32624E



www.landa.com

LANDA®

Industrial Pressure Washers
...Built Right to Do the Job Right

Since 1969

SLX-SLT

The Only Portable Hot Water Pressure Washer
that Delivers 200°F Cleaning at up to 9.8 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil

WHY CHOOSE LANDA'S SLX or SLT

When it comes to heavy-duty grease or grime, most high-volume, hot water pressure washers fall short with their 150°F water. Landa's SLX, and smaller SLT, are the first power washers ever designed to deliver a high-volume flow at 200°F, hot enough to melt the toughest of oily messes. The SLX delivers enough hot water flow—up to 9.8 GPM—that you can operate two spray guns at the same time! Other benefits include:

QUALITY: Packed with Landa quality throughout, the SLX and SLT feature a top-of-the-line, belt-drive Landa Pump with 7-year warranty and low RPM for extended life, as well as a giant Schedule 80 heating coil, made of up to 300 ft. of 3/4-inch steel pipe with 5-year warranty.

DURABILITY: Extraordinarily rugged frame is made of 2-by-4-inch box steel with an all-metal power platform cushioned by 10 vibration isolators to minimize frame stress.

EFFICIENT: The SLX-SLT is heated by a high-efficiency Landa SureFire or Beckett burner with adjustable numbered dial-in air flow. The 3/4" heating coil is amazingly efficient due to its unique "breathing" design so it heats quieter while promoting optimum heat exchange.

FUNCTIONAL: The SLX-SLT has a remarkably compact footprint, is certified to UL-1776 safety standards, has six forklift guides for portability, and the recessed control panel is ideally positioned for curb access when the unit is mounted on a trailer or truck bed.

SLX and SLT Specifications

| Model No. | GPM | PSI | Engine | CCs | Engine Fuel | Gas Tank | Diesel Tank | Pump RPM | BTU's | L x W x H | SHIP WT. |
|--------------|------|-------|--------------|------|-------------|----------|-------------|----------|---------|-----------------|------------|
| SLX10-25324E | 9.5 | 2,500 | Honda GX660 | 688 | Gasoline | 16 | 30 | 1,560 | 887,000 | 65" x 36" x 58" | 2,020 lbs. |
| SLX10-32624E | 9.8 | 3,200 | Kubota D1105 | 1123 | Diesel | N/A | 40 | 1,470 | 887,000 | 65" x 36" x 61" | 2,120 lbs. |
| SLT6-32324E | 5.9 | 3,200 | Honda GX630 | 688 | Gasoline | 10 | 15 | 1,570 | 550,000 | 55" x 32" x 51" | 1,245 lbs. |
| SLT8-30324E | 7.8 | 3,000 | Honda GX660 | 688 | Gasoline | 10 | 15 | 1,470 | 728,000 | 55" x 32" x 51" | 1,230 lbs. |
| SLT6-32624E | 6.25 | 3,200 | Kubota D1105 | 1123 | Diesel | N/A | 26 | 1,600 | 588,000 | 62" x 32" x 57" | 1,745 lbs. |
| SLT8-32624E | 8.0 | 3,200 | Kubota D1105 | 1123 | Diesel | N/A | 26 | 1,560 | 728,000 | 62" x 32" x 57" | 1,811 lbs. |

E=Electric Start

Note: Landa is constantly improving and updating its products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. Landa product performance is certified by the Cleaning Equipment Trade Association (CETA) to be within 5% of listed specifications.

Field-Installed Kits

| | |
|-------------------------------|-------------|
| Float Tank w/ Inlet Injection | 8.920-751.0 |
| Downstream Injector | 8.904-456.0 |
| Steam Valve | 8.920-977.0 |

LANDA®

Distributed by:



Power Wash Detergents:

Landa has an extensive line of detergents formulated specifically for use with hot water pressure washers such as the SLX and SLT

www.landa.com