

HOT SHOT SERIES



4230VB-30G1



4230VB-30G3

EZ ACCESS FLOAT TANK W/ SLIDE OUT FEATURE

STANDARD FEATURES

- Rugged powder coated steel roll cage frame w/ lifting hook & 13" flat free tires & threaded axles
- 4-wheel dimensions: 39" L x 31" W x 49" H
- Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade motors
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Low speed pump w/ thermo-sensor (prevents over heating in bypass mode)
- 12' power cord (no plug)

NOTE: All units are completely factory assembled, tested in the USA, and delivered ready to operate.

STANDARD ACCESSORIES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Adjustable high pressure chemical metering system
- 4 color-coded QC spray nozzles

AVAILABLE OPTIONS

ATK010 Inline Adjustable Thermostat.

BRK100 Brake Kit.
HRK415 Hose Reel Kit, 150' x 3/8" max.
w/ no add'l hose.

**AR and CAT pumps
available - consult factory**

4 WHEEL PORTABLE V-BELT DRIVE ELECTRIC MODELS

3230VB-25G1	3.0 GPM @ 2500 PSI	5.0 HP	230V/1PH/25A	GP Pump
4230VB-20G1	4.0 GPM @ 2000 PSI	5.0 HP	230V/1PH/25A	GP Pump
4230VB-20G3	4.0 GPM @ 2000 PSI	5.0 HP	230V/3PH/12A	GP Pump
5230VB-15G1	5.0 GPM @ 1500 PSI	5.0 HP	230V/1PH/25A	GP Pump
4230VB-30G1	4.0 GPM @ 3000 PSI	7.5 HP	230V/1PH/33A	GP Pump
4230VB-30G3	4.0 GPM @ 3000 PSI	7.5 HP	230V/3PH/17A	GP Pump
5230VB-20G1	5.0 GPM @ 2000 PSI	7.5 HP	230V/1PH/33A	GP Pump
4230VB-35G1	4.0 GPM @ 3500 PSI	10 HP	230V/1PH/46A	HP Pump
4230VB-35G3	4.0 GPM @ 3500 PSI	10 HP	230V/3PH/23A	HP Pump
5230VB-30G1	5.0 GPM @ 3000 PSI	10 HP	230V/1PH/46A	HP Pump
5230VB-30G3	5.0 GPM @ 3000 PSI	10 HP	230V/3PH/23A	HP Pump

**CALL FOR
PRICING**

563-299-4887